


FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- For surface mounted applications
- Super fast switching for high efficiency
- Low reverse leakage
- Built-in strain relief, ideal for automated placement
- High forward surge current capability
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- Glass passivated chip junction

MECHANICAL DATA

- Case:** JEDEC DO-214AB molded plastic body over passivated chip
- Terminals:** Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity:** Color band denotes cathode end
- Mounting Position:** Any
- Weight:** 0.007 ounce, 0.25grams



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	ES3M	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	Volts
Maximum RMS Voltage	V_{RMS}	700	Volts
Maximum DC Blocking Voltage	V_{DC}	1000	Volts
Maximum Average Forward Rectified Current At $T_L=105$ (NOTE 1)	$I_{(AV)}$	3.0	Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	100	Amps
Maximum Instantaneous Forward Voltage at 3.0A	V_F	1.7	Volts
Maximum DC Reverse Current at rated DC Blocking Voltage at	$T_A = 25$	10	μA
	$T_A = 125$	200	
Maximum Reverse Recovery Time Test conditions $I_F=0.5A$, $I_R=1.0A$, $I_{RR}=0.25A$	t_{rr}	75	nS
Typical Junction Capacitance (Measured at 1.0MHz and applied reverse voltage of 4.0V)	C_J	50	pF
Typical Thermal Resistance (Note 1)	$R_{\theta A}$	55	/W
	$R_{\theta L}$	17	
Operating Junction Temperature	T_J	(-55 to +150)	
Storage Temperature Range	T_{STG}	(-55 to +150)	

Notes:

- Thermal resistance from Junction to ambient and from junction to lead mounted on P.C.B. with 0.3×0.3! (8.0 ×8.0mm) copper pad areas.



FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC

